

NOTES: ANCHORS AND SHIMS SUPPLIED BY SEVES GLASS BLOCK INC. POSITIONING OF GLASS BLOCK WITHIN THE OPENING CAN BE PLACED WHERE REQUIRED

REVISIONS		
REV	DESCRIPTION	DATE
-	-	-

CMU LINTEL \ BOND BEAM  
**HEAD, JAMB- SIMILAR**

BACKER ROD AND SEALANT  
TYPICAL INTERIOR AND EXTERIOR  
SIDE TO BE SUPPLIED BY OTHERS

SEVES GLASS BLOCK TORNADO  
RESISTANT HIGH PERFORMANCE  
WINDOW

BEAD BLAST FINISH TYPICAL ON  
EXPOSED INTERIOR SURFACES

SANTOPRENE BOOT

HILTI HUS-EZ, KH-EZ  
 $\frac{3}{8} \times 3 \frac{1}{2}$ " ANCHORS AT 16"  
OC AND MAX. OF 4" FROM EACH  
CORNER, AT HEAD, JAMB AND  
SILL  
SEALANT

**SILL**

**OVERALL UNIT DIMENSIONS:**

18 @ 24 1/4" X 16" 1/4"

**REQUIRED OPENINGS:**

24 3/4" (+0"/-1/4") X 16 3/4" (+0"/-1/4")

**ANCHOR LOCATIONS:**

(2) @ HEAD AND SILL,  
(2) @ EA. JAMB

SEALANT  
(SUPPLIED BY OTHERS)

1/4" (MAX) SHIM WITH SEALANT ON  
BOTH SIDES (SUPPLIED BY  
OTHERS)


8x8x3" SEVES GLASS BLOCK  
LAMINATED VISTABRIK

EPOXY GROUT, TYP

**APPROVAL**

6 1/2" FRAME DEPTH

**TYPICAL HEAD & SILL DETAIL**

	PROJECT	Lakeport State Park		
	TITLE	Lightwise Architectural System High Performance Tornado Resistant Window		
SCALE	3"=1'-0"	DTL. NO.	DWG. NO.	REV
BY	RJB	DATE	5-28-19	SHEET 1 of 1

CONFIDENTIAL - PROPRIETARY  
THESE DRAWINGS WERE CREATED BY AND REMAIN THE PROPERTY OF SEVES GLASS BLOCK INC. UNAUTHORIZED DISCLOSURE, DISTRIBUTION OR COPYING OF THESE DRAWINGS IS STRICTLY PROHIBITED.  
THE FOLLOWING DETAILS ILLUSTRATE DESIGN INTENT; VARIATIONS MAYBE ACCEPTABLE.  
PLEASE CONTACT SEVES GLASS BLOCK TECHNICAL DEPARTMENT FOR FURTHER CONSULTATION